



EB
Eddi Bressan

PRECISION MECHANICAL COMPONENTS



List of machines

- EB** 5-axis Vertical Machining Center **OKUMA MU-400VA**
(work area: X 762 mm; Y 460 mm; Z 460 mm)
- EB** 5-axis Vertical Machining Center **MAZAK VARIAXIS J-500/5X**
(work area: X 350 mm; Y 550 mm; Z 510 mm)
- EB** 5-axis Vertical Machining Center **MAZAK VARIAXIS J-500**
(work area: X 350 mm; Y 550 mm; Z 510 mm)
- EB** Horizontal Machining Center **OKUMA MA50-HA** (with Pallet Changer)
2X (work area: X 700 mm; Y 800 mm; Z 700 mm)
- EB** Vertical Machining Center **OKUMA MF-46 VA** (with Pallet Changer)
2X (work area: X 762 mm; Y 460 mm; Z 460 mm)
- EB** Vertical Machining Center **OKUMA MX45VAE** (CNC rotary table)
(work area: X 760 mm; Y 460 mm; Z 450 mm)
- EB** Vertical Machining Center **OKUMA MX45VAE**
(work area: X 760 mm; Y 460 mm; Z 450 mm)
- EB** Vertical Machining Center **BROTHER TC S 2C-O** (CNC rotary table)
(work area: X 700 mm; Y 400 mm; Z 300 mm)
- EB** Vertical Machining Center **BROTHER TC-R2B** (with Pallet Changer)
2 X (work area: X 420 mm; Y 320 mm; Z 410 mm)
- EB** Multitasking Turning/Milling **MAZAK INTEGREGX J-200**
(max. bar capacity \varnothing 52 mm; main spindle \varnothing 210 mm)
- EB** Multitasking Turning/Milling **OKUMA U3000**
(max. bar capacity \varnothing 52 mm; main spindle \varnothing 210 mm)
(max. bar capacity \varnothing 52 mm; secondary spindle \varnothing 210 mm)
- EB** Multitasking Turning/Milling Center **OKUMA MULTUS B300W**
(max. bar capacity \varnothing 70 mm; main spindle \varnothing 250 mm)
(max. bar capacity \varnothing 52 mm; secondary spindle \varnothing 210 mm)
- EB** Lathe **OKUMA LB3000 EX MYW**
(max. bar capacity \varnothing 52 mm; main spindle \varnothing 210 mm)
(max. bar capacity \varnothing 52 mm; secondary spindle \varnothing 210 mm)
- EB** Lathe **MORI SEIKI RL-253**
(Twin spindle \varnothing 250 mm; with gantry loader)
- EB** Lathe **OKUMA LB3000 EX**
(max. bar capacity \varnothing 52 mm; spindle \varnothing 210 mm; L. 500 mm)
- EB** Lathe **OKUMA LB300**
(max. bar capacity \varnothing 70 mm; spindle \varnothing 250 mm; L. 500 mm)
- EB** Lathe **OKUMA LB300**
(max. bar capacity \varnothing 52 mm; spindle \varnothing 210 mm; L. 500 mm)

Measuring instruments

- EB** 3D Measuring Machine **ZEISS CONTURA G2**
(work area: X 700 mm; Y 1000 mm; Z 500 mm)

Laser Marking Machine

- EB** Fiber laser marking machine **FOBA LASER M2000-P**
(work area: X 315 mm; Y 225 mm; Z 590 mm; rotary table;
vision system IMP2 - New Lightning)

Software

- EB** Program and simulation system CAD/CAM 5-axis HyperMILL, OPEN MIND